

## Seat Belts for Forklift

Forklift Seat Belts - Explained in the Regulation guidelines are the use of seatbelts and operator restraints on lift trucks. It states that the liability falls on the employers' to make sure that every machinery, piece of equipment and device is used properly utilized according to the instructions of the producer.

Rough Terrain forklifts ought to meet the guidelines of ANSI Standard ASME B56.6-1992 regarding their maintenance, inspection, fabrication, use and design.

Mobile machinery like side boom tractors together with a Rollover Protective Structure (ROPS), should contain seat belts which meet the Society of Automotive Engineers safety requirements; Society of Automotive Engineers Standard J386 JUN93, Operator Restraint System for Off-Road Work Machines. If whatever mobile machine includes seat belts required by law, the operator and subsequent passengers should make sure they use the belts each time the motor vehicle is in motion or engaged in operation because this could cause the machine to become unbalanced and hence, unsafe.

If a seat belt or other operator restraint is required on a lift truck.

The seat belt requirements while operating a lift truck depend on different factors. Whether the lift truck is equipped along with a Rollover Protective Structure, the kind of lift truck itself and the year the forklift was actually manufactured all contribute to this determination. The manufacturer's instructions and the requirements of the applicable standard are referenced in the Regulation.

With regards to powered industrial lift trucks, ANSI Standard ASME B56.1-1993 refers to a driver restraint device, enclosure or system. An operator restraint device, system, or enclosure is intended so as to assist the operator in lessening the probability of entrapment of the torso and/or head between the truck and the ground in the event of a tip over. The system or restraint device may comprise a seat belt, though a seat belt is not essentially a part of such device or system.